

FOAM FIRE EXTINGUISHERS

- Available in 2, 3, 6 and 9 litre sizes
- 5-year warranty
- Kitemarked to BS EN 3
- Milieukeur approved
- 6ltr foam is MED approved
- UKCA/CE approved
- Spray nozzle
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Complete with wall bracket (6 and 9ltr)
- Complete with wire bracket (2ltr)
- Removable pressure gauge
- Fitted with safety pressure relief valve
- Passed the 35kv conductivity of discharge test



	TITANPSE06-01	TITANPSE06-04	TITANPSE06-02	TITANPSE06-03
Capacity	2 litres	3 litres	6 litres	9 litres
Fire rating	8A 55B	13A 89B	21A 183B	21A 233B
Extinguishing medium	AFFF (Foam)	AFFF (Foam)	AFFF (Foam)	AFFF (Foam)
Cylinder height	400mm	442mm	543mm	555mm
Diameter	115mm	140mm	150mm	194mm
Filled weight	3.70kg	5.52kg	9.25kg	13.25kg
Working pressure	13.50 bar	15.00 bar	15.00 bar	13.50 bar
Temperature range	+5°C-+60°C	+5°C-+60°C	+5°C-+60°C	+5°C-+60°C
Pressuring gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen

