

## WATER FIRE EXTINGUISHERS

- Standard water available in 6 and 9 litre sizes
- High performance water with additive available in 3 and 6 litre sizes
- 5-year warranty
- Kitemarked to BS EN 3
- 3 litre and 6 litre water with additive are Milieukeur approved
- 6 and 9 litre water and 6 litre water with additive are MED approved
- UKCA/CE approved
- Spray nozzle
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Removable pressure gauge
- Protective plastic base
- Fitted with safety pressure relief valve
- Passed the 35kv conductivity of discharge test



	TITANPSE05-02	TITANPSE05-01	TITANPSE05-04PLUS	TITANPSE05-03PLUS
Capacity	6 litres	9 litres	3 litres	6 litres
Fire rating	13A	21A	13A	34A
Extinguishing medium	Water	Water	Water with additive	Water with additive
Cylinder height	545mm	555mm	442mm	550mm
Diameter	150mm	180mm	140mm	162mm
Filled weight	9.25kg	13.25kg	5.80kg	9.25kg
Working pressure	13.50 bar	13.50 bar	13.50 bar	13.50 bar
Temperature range	+5°C-+60°C	+5°C-+60°C	+5°C-+60°C	+5°C-+60°C
Pressuring gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen

