

ABC POWDER FIRE EXTINGUISHERS


- BSI Kitemark
- UKCA approved
- CE approved
- Compliant with Merchant Shipping (Marine Equipment) Regulation. Conformity Assessment Procedure Module B
- High fire ratings
- 1, 2 and 3kg c/w wire bracket
- 5-year warranty

	TITAN BKP1	TITAN BKP2	TITAN BKP3	TITAN BKP4	TITAN BKP6	TITAN BKP9	TITAN BKP12
Capacity	1kg	2kg	3kg	4kg	6kg	9kg	12kg
Fire rating	8A 34B	13A 55B	21A 70B	27A 113B	34A 183B	43A 183B	55A 233B
Extinguishing medium	40% ABC Powder	40% ABC Powder	40% ABC Powder	40% ABC Powder	40% ABC Powder	40% ABC Powder	40% ABC Powder
Cylinder height	277mm	306.5mm	308mm	360mm	427mm	453mm	503mm
Diameter	85mm	110mm	130mm	140mm	160mm	185mm	190mm
Filled weight	2.25kg	3.50kg	5.00kg	6.60kg	9.45kg	13.20kg	16.80kg
Volume	1.30 litres	2.35 litres	3.50 litres	4.70 litres	7.60 litres	10.20 litres	12.50 litres
Working pressure	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar
Test pressure	30 bar	30 bar	30 bar	30 bar	30 bar	30 bar	30 bar
Temperature range	-20°C-+60°C	-20°C-+60°C	-20°C-+60°C	-20°C-+60°C	-20°C-+60°C	-20°C-+60°C	-20°C-+60°C
Pressuring gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen
Box dimensions	275 x 205 x 360mm (6 pieces)	345 x 260 x 390mm (6 pieces)	140 x 140 x 385mm	160 x 160 x 475mm	170 x 170 x 535mm	195 x 195 x 560mm	200 x 200 x 610mm

