









6kg Powder

The TITAN CORE 6kg Powder fire extinguisher is suitable for tackling Class A, B and C fire risks (combustible materials, flammable liquids and flammable gases) and is safe for use on electrical equipment. Not recommended for indoor use.

- Fire rating: 43A 233B/C
- BS EN 3 Kitemark
- UKCA/CE approved
- Supplied with bracket
- Corrosion-resistant finishes
- Safe for use on electrical equipment
- 5-year warranty





TITANCOREP6 Extinguishing medium ABC Powder Capacity 6kg Fire rating 43A 233B/C Cylinder material DC01 Steel Maximum working pressure 18 bar Test pressure 29 bar Cylinder height 444mm Diameter 160mm Filled weight 9.30kg Temperature range -20°C-+60°C Volume 7.80 litres BS EN 3 Kitemark ✓		
Capacity 6kg Fire rating 43A 233B/C Cylinder material DC01 Steel Maximum working pressure 18 bar Test pressure 29 bar Cylinder height 444mm Diameter 160mm Filled weight 9.30kg Temperature range -20°C-+60°C Volume 7.80 litres BS EN 3 Kitemark ✓		TITANCOREP6
Fire rating 43A 233B/C Cylinder material DC01 Steel Maximum working pressure 18 bar Test pressure 29 bar Cylinder height 444mm Diameter 160mm Filled weight 9.30kg Temperature range -20°C-+60°C Volume 7.80 litres BS EN 3 Kitemark ✓	Extinguishing medium	ABC Powder
Cylinder material DC01 Steel Maximum working pressure 18 bar Test pressure 29 bar Cylinder height 444mm Diameter 160mm Filled weight 9.30kg Temperature range -20°C-+60°C Volume 7.80 litres BS EN 3 Kitemark ✓	Capacity	6kg
Maximum working pressure18 barTest pressure29 barCylinder height444mmDiameter160mmFilled weight9.30kgTemperature range-20°C-+60°CVolume7.80 litresBS EN 3 Kitemark✓	Fire rating	43A 233B/C
Test pressure 29 bar Cylinder height 444mm Diameter 160mm Filled weight 9.30kg Temperature range -20°C-+60°C Volume 7.80 litres BS EN 3 Kitemark ✓	Cy l inder material	DC01 Steel
Cylinder height444mmDiameter160mmFilled weight9.30kgTemperature range-20°C-+60°CVolume7.80 litresBS EN 3 Kitemark√	Maximum working pressure	18 bar
Diameter160mmFilled weight9.30kgTemperature range-20°C-+60°CVolume7.80 litresBS EN 3 Kitemark√	Test pressure	29 bar
Filled weight 9.30kg Temperature range -20°C-+60°C Volume 7.80 litres BS EN 3 Kitemark ✓	Cylinder height	444mm
Temperature range -20°C-+60°C Volume 7.80 litres BS EN 3 Kitemark ✓	Diameter	160mm
Volume 7.80 litres BS EN 3 Kitemark ✓	Filled weight	9.30kg
BS EN 3 Kitemark ✓	Temperature range	-20°C-+60°C
	Volume	7.80 litres
	BS EN 3 Kitemark	✓
UKCA/CE ✓	UKCA/CE	✓
Pallet quantity 72	Pa ll et quantity	72