

## PLAIN WATER FIRE EXTINGUISHERS



- Water fire extinguishers: filled with plain water contains no fluorine, silicone or PFAS, PFOA or PFOS
- Stored pressure 3ltr, 6ltr and 9ltr available
- 35kv di-electrical test
- Supplied with bracket
- Kitemarked to BS EN 3 (6/9ltr)
- UKCA/CE approved
- 5-year warranty



	TITANCOREW3	TITANCOREW6	TITANCOREW9
Capacity	3 litres	6 litres	9 litres
Fire rating	13A	13A	21A
Extinguishing medium	Plain water	Plain water	Plain water
Cylinder height	340mm	448mm	519mm
Cylinder diameter	130mm	162mm	184mm
Filled weight	5.00kg	10.30kg	14.50kg
Working pressure	12 bar	12 bar	12 bar
Test pressure	27 bar	27 bar	27 bar
Temperature range	+5°C-+60°C	+5°C-+60°C	+5°C-+60°C
Pressuring gas	Nitrogen	Nitrogen	Nitrogen
Cylinder material	ST12 Steel	ST12 Steel	ST12 Steel
Volume	3.60 litres	7.80 litres	11.20 litres
Pallet quantity	108	72	40
BS EN 3 Kitemark	X	✓	✓
UKCA/CE	✓ (CE)	✓	✓