TITAN BK FLUORINE-FREE FIRE EXTIGUISHERS AND TROLLIES

	TITANBKFF2	TITANBKFF3	TITANBKFF50	TITANBKFF100	TITANBKFF135
Size	2L	3L	50L	100L	135L
Fire rating	8A 34B	13A 55B	A II B	A IV B	A IV B
Approvals	BS EN 3 Kitemark UKCA | CE	BS EN 3 Kitemark UKCA | CE	BS EN 3 Kitemark UKCA | CE	BS EN 3 Kitemark UKCA | CE	BS EN 3 Kitemark UKCA | CE
Fire extinguishing agent	3% Furex Pure B + 1.5% Furex A + 95.5% water	3% Furex Pure B + 1.5% Furex A + 95.5% water	2% Furex Pure B + 98% water	2% Furex Pure B + 98% water	2% Fure Pure B + 98% water
Capacity (litres)	2.5 litres	3.7 litres	66.5 litres	130 litres	171 litres
Discharge time (seconds)	12	20	170	350	550
Working pressure (bar)	12	12	15	15	15
Test pressure (bar)	30	30	30	30	30
Temperature range	+5°C-+60°C	+5°C-+60°C	+5°C-+60°C	+5°C-+60°C	+5°C-+60°C
Cylinder height (mm)	326	322.50	918	927	1184
Cylinder diameter (mm)	110	130	320	458	458
Cylinder material	Carbon steel	Carbon steel	Carbon steel	Carbon steel	Carbon steel
Pressurising gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen

Express Fire Equipment Ltd., Units 3, 4, 6 and 10 Mersey Road Industrial Estate, Mersey Road North, Failsworth, Manchester, M35 9LU.
Tel: 0161 688 5050 | Web: www.expressfire.com | Email: info@expressfire.com